

Amendments To The Specification:

Please replace paragraph [0001] with the following:

This patent application takes priority under 35 U.S.C. 119(e) to (i) U.S. Provisional Patent Application No.: 60/467,804, filed on May 1, 2003 (Attorney Docket No. GENSP013P) entitled "DIGITAL/ANALOG VIDEO INTERCONNECT AND METHODS OF USE THEREOF" by Kobayashi, (ii) U.S. Provisional Patent Application No.: 60/504,060 (Attorney Docket No. GENSP013P2) filed on September 18, 2003, entitled "DIGITAL/ANALOG VIDEO INTERCONNECT AND METHODS OF USE THEREOF" by Kobayashi, (iii) U.S. Provisional Patent Application No.: 60/474,085 (Attorney Docket No. GENSP014P) filed on May 28, 2003, entitled "DIGITAL/ANALOG VIDEO INTERCONNECT AND METHODS OF USE THEREOF" by Kobayashi, and (iv) U.S. Provisional Patent Application No.: 60/474,084 (Attorney Docket No. GENSP015P) filed on May 28, 2003, entitled "SIMPLE ENUMERATION METHOD FOR THE LINK CLOCK RATE AND THE PIXEL/AUDIO CLOCK RATE" by Kobayashi each of which are hereby incorporated by reference herein in their entirety. This application is also related to the following co-pending U.S. Patent applications, which are filed concurrently with this application and each of which are herein incorporated by reference, (i) U.S. Patent Application No. 10/726,802 (Attorney Docket No.: GENSP014), entitled "METHOD OF ADAPTIVELY CONNECTING A VIDEO SOURCE AND A VIDEO DISPLAY" naming Kobayashi as inventor; (ii) U.S. Patent Application No. 10/726,438 (Attorney Docket No.: GENSP104), entitled "METHOD AND APPARATUS FOR EFFICIENT TRANSMISSION OF MULTIMEDIA DATA PACKETS" naming Kobayashi as inventor; (iii) U.S. Patent Application No. 10/726,794, (Attorney Docket No.: GENSP013), entitled "PACKET BASED VIDEO DISPLAY INTERFACE AND METHODS OF USE THEREOF", naming Kobayashi as inventor; (iv) U.S. Patent Application No. 10/726,440 (Attorney Docket No.: GENSP105), entitled "PACKET BASED MONITOR TRAINING IN A VIDEO SYSTEM", naming Kobayashi as inventor; (v) U.S. Patent Application No. 10/726,350 (Attorney Docket No.: GENSP106), entitled "TECHNIQUES FOR REDUCING MULTIMEDIA DATA PACKET OVERHEAD", naming Kobayashi as inventor; (vi) U.S. Patent Application No. 10/726,362 (Attorney Docket No.: GENSP107), entitled "PACKET BASED CLOSED LOOP VIDEO DISPLAY INTERFACE WITH PERIODIC STATUS CHECKS", naming Kobayashi as inventor; (vii) U.S. Patent Application No. 10/726,895 (Attorney Docket No.: GENSP108), entitled "MINIMIZING BUFFER REQUIREMENTS IN A DIGITAL VIDEO SYSTEM",

naming Kobayashi as inventor; (viii) U.S. Patent Application No. 10/726,441 (Attorney Docket No.: GENSP109), entitled "VIDEO INTERFACE ARRANGED TO PROVIDE PIXEL DATA INDEPENDENT OF A LINK CHARACTER CLOCK", naming Kobayashi as inventor; and (ix) U.S. Patent Application No. 10/726,934 (Attorney Docket No.: GENSP110), entitled "ENUMERATION METHOD FOR THE LINK CLOCK RATE AND THE PIXEL/AUDIO CLOCK RATE", naming Kobayashi as inventor. This application is also related to the following co-pending applications: (x) U.S. Patent Application No. 10/909,103 (Attorney Docket No.: GENSP112), entitled "USING PACKET TRANSFER FOR DRIVING LCD PANEL DRIVER ELECTRONICS" filed July 29, 2004, naming Kobayashi as inventor; **(xi) U.S. Patent Application No. 10/909,027 (Attorney Docket No.: GENSP113), entitled "BYPASSING PIXEL CLOCK GENERATION AND CRTC CIRCUITS IN A GRAPHICS CONTROLLER CHIP" filed July 29, 2004, naming Kobayashi as inventor; and** ~~(xi)~~ **(xii)** U.S. Patent Application No. 10/909,085 (Attorney Docket No.: GENSP127), entitled "PACKET BASED STREAM TRANSPORT SCHEDULER AND METHODS OF USE THEREOF" filed July 29, 2004, naming Kobayashi as inventor.

Please replace paragraph [0025] with the following:

Other embodiments describe a simple enumeration method for the link rate and the pixel/audio clock rate. ~~It has been researched and understood that all the~~ **All** standard pixel/audio clock frequencies that exist today are a subset of the following master frequency: **23.76 GHz. In accordance with an embodiment of the invention, this master frequency (23.76 GHz) can be expressed as a function of four parameters A, B, C, and D as:**

$$\underline{23.76\text{GHz} = 2^A \times 3^B \times 5^C \times 11^D \text{ Hz where}}$$

$$\underline{A=10, B=3, C=7, D=1,}$$

$$(23.76\text{GHz} = 2^{10} \times 3^3 \times 5^7 \times 11^1 \text{ Hz}).$$

This means that a pixel (or audio) clock rate can be expressed **as a subset of the master frequency** with **these** four parameters, A, B, C, and D **(where A ≤ 10, B ≤ 3, C ≤ 7, D ≤ 1) as**

$$\text{Pixel } \underline{\text{(or audio)}} \text{ clock rate} = 2^A \times \underline{x} 3^B \times 5^C \times 11^D.$$

It should be noted that since A is less than or equal to 10, A can be expressed in 4 bits, and since B is less than or equal to 3, B can be expressed using as 2 bits, C as 3 bits and D as 1 bit. A = 4 bits, B = 2 bits, C = 3 bits, and D = 1 bit.

Please replace paragraph [0025] with the following:

Even for a link whose link rate (which is the serial link bit rate / 10 for a link that uses 10-bit character such as 8B/10B characters) may be different from the pixel clock rate, there is a benefit in defining the link rate with these four parameters, A', B', C', and D': The benefit is the simplicity in regenerating pixel/audio clocks from a link clock. For example, let's say the link rate is set as A' = 6, B' = 3, C' = 7, and D' = 0 (i.e., LR = $2^6 \times 3^3 \times 5^7 \times 11^0$) and the corresponding link rate is 135MHz. However, suppose the pixel clock rate is set as A = 8, B = 3, C = 6, and D = 0 (i.e., PC = $2^8 \times 3^3 \times 5^6 \times 11^0$) (= and the corresponding pixel clock rate is 108MHz), then the pixel clock can be generated from link clock by the following equation

$$\begin{aligned} \text{Pixel clock rate} &= (\text{link rate}) \times (2^{A-A'}, 3^{B-B'}, 5^{C-C'}, \text{ and } 11^{D-D'}). \text{ For the above example,} \\ (\text{Pixel clock rate/Link rate}) &= (2^8 \times 3^3 \times 5^6 \times 11^0) / (2^6 \times 3^3 \times 5^7 \times 11^0) \text{ or} \\ \text{Pixel clock rate} &= (\text{Link rate}) \times (2^2) \times (3^0) \times (5^{-1}) \times (11^0) = \text{Link rate} \times (.8). \end{aligned}$$

~~as pixel clock rate is equal to the link rate * 22 / 51.~~

